



所有尺寸：毫米

公制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码	A Max.	最小板厚	板开口尺寸 +0.08	C Max.	H ± 0.25	孔中心到板边缘的最小距离
		螺母材料									
		碳钢	不锈钢								
M2x0.4	FC	F	M2	1	1.53	1.53-2.3	4.37	4.35	4.8	6.0	
				2	2.3	2.32Min.					
M2.5x0.45	FC	F	M2.5	1	1.53	1.53-2.3	4.37	4.35	4.8	6.0	
				2	2.3	2.32Min.					
M3x0.5	FC	F	M3	1	1.53	1.53-2.3	4.37	4.35	4.8	6.0	
				2	2.3	2.32Min.					
M4x0.7	FC	F	M4	1	1.53	1.53-2.3	7.37	7.35	7.9	7.2	
				2	2.3	2.32Min.					
M5x0.8	FC	F	M5	1	1.53	1.53-2.3	7.92	7.9	8.7	8.0	
				2	2.3	2.32Min.					
M6x1.0	FC	F	M6	3	3.05	3.18-3.94	8.74	8.72	9.5	8.8	
				4	3.84	3.96-4.72					
				5	4.63	4.75Min.					

所有尺寸：英寸

英制螺纹	螺纹规格	规格型号		螺纹代码	尾缀码	A Max.	最小板厚	板开口尺寸 +.003/-0	C Max.	H ± .01	孔中心到板边缘的最小距离
		螺母材料									
		碳钢	不锈钢								
.086-56 (#2-56)	FC	F	256	1	.060	.060-.090	.172	.171	.188	.23	
				2	.090	.091Min.					
.112-40 (#4-40)	FC	F	440	1	.060	.060-.090	.172	.171	.188	.23	
				2	.090	.091Min.					
.138-32 (#6-32)	FC	F	632	1	.060	.060-.090	.213	.212	.250	.27	
				2	.090	.091Min.					
.164-32 (#8-32)	FC	F	832	1	.060	.060-.090	.290	.289	.312	.28	
				2	.090	.091Min.					
.190-32 (#10-32)	FC	F	032	1	.060	.060-.090	.312	.311	.343	.31	
				2	.090	.091Min.					
.250-20 (1/4-20)	FC	F	0420	3	.120	.125-.155	.344	.343	.375	.34	
				4	.151	.156-.186					
				5	.182	.187Min.					

- (1) 为了达到最好的性能，我们建议你根据实际板厚选择对应的螺母
- (2) 为了最大限度的减少安装的板的变形，以及获得最好的性能，建议螺母安装需要和边缘保持足够的距离