



命名规则	FE - M3	- MD	
	FE0 - M3	- MD	
	UL - M3	- 1 - MD	
	↓	↓	
产品类型	螺纹代码	尾缀代码	表面处理类型

所有尺寸：毫米

公制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码 (2)	A Max.	最小板厚	板开口尺寸 +0.08	C -0.13	D Max.	E ± 0.13	T +0.4	孔中心到板边缘最小距离	模具底模孔 Max.
		非自锁 (3)	自锁											
公制螺纹	M2x0.4	U	UL	M2	1	0.76	0.76-0.91	3.61	3.6	2.5	4.07	1.65	2.8	2.5
	M3x0.5	FE0X	FE0	M3		1.02	0.99-1.14	4.39	4.37	3.96	4.88	1.9	3.6	3.5
		FEX	FE			1.53	1.5-1.78							
	M4x0.7	FE0X	FE0	M4		1.02	0.99-1.14	7.39	7.37	5.23	8.17	2.55	5.2	4.5
		FEX	FE			1.53	1.5-1.78							
	M5x0.8	FE0X	FE0	M5		1.02	0.99-1.14	7.39	7.37	6.48	8.17	3.05	5.2	5.5
		FEX	FE			1.53	1.5-1.78							
	M6x1.0	FEX	FE	M6		1.53	1.5-1.78	8.74	8.72	7.72	9.74	3.3	7.1	6.5

所有尺寸：英寸

英制螺纹	螺纹规格	规格型号		螺纹代码	尾缀代码 (2)	A Max.	最小板厚	板开口尺寸 +.003 - .000	C +.000 - .005	D Max.	E ± .005	T +.015 - .000	孔中心到板边缘最小距离	安装下模沉孔直径 Max.	
		非自锁 (1)	自锁												
英制螺纹	.060-80 (#0-80)	U	UL	080	0	.020	.019-.022	.110	.1095	.076	.125	.050	.09	.080	
	.073-64 (#1-64)	U	UL	164	0	.020	.019-.022	.110	.1095	.090	.125	.050	.09	.093	
	.086-56 (#2-56)	U	UL	256		0	.020	.019-.022	.144	.1435	.106	.160	.065	.11	.106
						1	.030-.036								
	.112-40 (#4-40)	FE0X	FE0	440		.040	.039-.045	.172	.171	.145	.192	.065	.14	.132	
		FEX	FE			.060	.059-.070								
	.138-32 (#6-32)	FE0X	FE0	632		.040	.039-.045	.213	.212	.180	.244	.075	.17	.158	
		FEX	FE			.060	.059-.070								
	.164-32 (#8-32)	FE0X	FE0	832		.040	.039-.045	.290	.289	.215	.322	.090	.20	.184	
		FEX	FE			.060	.059-.070								
	.190-32 (#10-32)	FE0X	FE0	032		.040	.039-.045	.290	.289	.245	.322	.110	.20	.210	
		FEX	FE			.060	.059-.070								
1/4-20	FEX	FE	0420		.060	.059-.070	.344	.343	.318	.384	.120	.28	.270		
1/4-28														0428	

- (1) 允许2B的通规可以止，但是3A等级的螺丝必须可以通过。
- (2) 尾缀代码只适用于U、UL系列
- (3) 允许6H的通规可以不通，但是4h的螺钉必须可以通过。