



所有尺寸：毫米

公制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± 0.4 (长度单位为毫米)										最小 板厚	板开口 尺寸 +0.08	H ± 0.4	S 最大值	孔中心到 板边缘的 最小距离
		碳钢	不锈钢		6	8	10	12	15	18	-	-	-	-					
	M2.5x0.45	FHL	FHLS	M2.5	6	8	10	12	15	18	-	-	-	-	1.0	2.5	3.15	2.1	2.8
	M3x0.5	FHL	FHLS	M3	6	8	10	12	15	18	20	25	-	-	1.0	3.0	3.65	2.1	3.3
	M3.5x0.6	FHL	FHLS	M3.5	6	8	10	12	15	18	20	25	30	-	1.0	3.5	4.15	2.3	3.8
	M4x0.7	FHL	FHLS	M4	6	8	10	12	15	18	20	25	30	35	1.0	4.0	4.65	2.4	4.3
	M5x0.8	FHL	FHLS	M5	-	8	10	12	15	18	20	25	30	35	1.0	5.0	5.90	2.7	5.6

所有尺寸：英寸

英制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± .015 (长度=长度编码/16英寸)										最小 板厚	板开口 尺寸 +.003 -.000	H ± .015	S 最大值	孔中心到 板边缘的 最小距离
		碳钢	不锈钢		.250	.312	.375	.500	.625	.750	.875	1.000	1.250	1.500					
	.086-56 (#2-56)	FHL	FHLS	256	4	5	6	8	10	12	-	-	-	-	.04	.085	.112	.080	.098
	.112-40 (#4-40)	FHL	FHLS	440	4	5	6	8	10	12	14	16	-	-	.04	.111	.138	.085	.124
	.138-32 (#6-32)	FHL	FHLS	632	4	5	6	8	10	12	14	16	20	24	.04	.137	.164	.090	.150
	.164-32 (#8-32)	FHL	FHLS	832	4	5	6	8	10	12	14	16	20	24	.04	.163	.190	.090	.176
	.190-32 (#10-32)	FHL	FHLS	032	-	5	6	8	10	12	14	16	20	24	.04	.189	.225	.100	.210