



所有尺寸：毫米

公制规格	螺纹尺寸 x 螺距	通孔直径 +.01/ -0.08	规格型号		螺纹 或 通孔 代码	长度“L” +/-0.13 (长度单位为毫米)								A Max.	最小 板厚	板开口 尺寸 +0.08	C ± 0.08	E ± 0.13	孔中心到 板边缘的 最小距离
			碳钢	不锈钢		3	4	6	8	10	12	14	16						
	M3x0.5	-	KFE	KFSE	M3	3	4	6	8	10	12	14	16	1.53	1.53	4.22	4.68	5.56	4.4
	-	3.6	KFE	KFSE	3.6	3	4	6	8	10	12	14	16	1.53	1.53	5.41	5.87	7.14	5.5
	-	4.2	KFE	KFSE	4.2	3	4	6	8	10	12	14	16	1.53	1.53	6.40	6.86	8.74	7.1
最小螺纹深度“F” Min						全螺纹				9.5 ± 0.4									

所有尺寸：英寸

英制规格	螺纹规格	通孔直径 +.004/ -.003	规格型号		螺纹 或 通孔 代码	长度“L” +/- .005 (螺柱长度=长度码/32英寸)								A Max.	最小 板厚	板开口 尺寸 +.003 -.000	C ± .003	E ± .005	孔中心到 板边缘的 最小距离
			碳钢	不锈钢		.125	.250	.375	.500	.625	.750	.875	1.0						
	.112-40 (#4-40)	-	KFE	KFSE	440	4	8	12	16	20	24	-	-	.060	.060	.166	.184	.219	.17
	.138-32 (#6-32)	-	KFE	KFSE	632	4	8	12	16	20	24	28	32	.060	.060	.213	.231	.281	.22
	-	.116	KFE	KFSE	116	4	8	12	16	20	24	-	-	.060	.060	.166	.184	.219	.17
	-	.143	KFE	KFSE	143	4	8	12	16	20	24	28	32	.060	.060	.213	.231	.281	.22
最小螺纹深度“F” Min						全螺纹			.375 ± .016			.375盲孔							