



所有尺寸：毫米

公制螺纹	螺纹尺寸 x 螺距	规格 型号	螺纹 代码	长度“L” +/-0.25 (长度单位为毫米)					A Max.	最小 板厚	板开口 尺寸 +0.08	H ± 0.25	S Max.	T ± 0.13	孔中心到 板边缘的 最小距离	
				6	8	10	12	15								18
	M3x0.5	KFH	M3	6	8	10	12	15	18	1.65	1.53	3.0	4.58	2.3	0.51	3.8
	M4x0.7	KFH	M4	6	8	10	12	15	18	1.65	1.53	4.2	5.74	2.3	0.51	5.1
	M5x0.8	KFH	M5	6	8	10	12	15	18	1.65	1.53	5.0	6.6	2.3	0.51	5.3

所有尺寸：英寸

英制螺纹	螺纹规格	规格 型号	螺纹 代码	长度“L” ± .010 (长度=长度编码/16英寸)					A Max.	最小 板厚	板开口 尺寸 +.003 -.000	H ± .010	S Max.	T ± .005	孔中心到 板边缘的 最小距离	
				.250	.312	.375	.500	.625								.750
	.112-40 (#4-40)	KFH	440	4	5	6	8	10	12	.065	.060	.120	.180	.09	.020	.15
	.138-32 (#6-32)	KFH	632	4	5	6	8	10	12	.065	.060	.140	.200	.09	.020	.19
	.164-32 (#8-32)	KFH	832	4	5	6	8	10	12	.065	.060	.166	.225	.09	.020	.20
	.190-32 (#10-32)	KFH	032	4	5	6	8	10	12	.065	.060	.189	.250	.09	.020	.20