



所有尺寸：毫米

公制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± 0.4 (长度单位为毫米)						最小 板厚	沉孔 直径 +0.08/ -0.0	沉孔的 最小深度 Min.	A Max.	E ± 0.25	C Max.	孔中心 与安装 板边缘 最小距离	
		螺钉材料			6	8	10	12	16	20								25
		铝合金	不锈钢															
M3x0.5	CHA	CHC	M3	6	8	10	12	16	20	-	1.60	4.37	1.10	1.04	5.21	4.35	4.00	
	CFHA	CFHC									2.40		1.91					1.80
M4x0.7	CHA	CHC	M4	6	8	10	12	16	20	25	1.60	7.37	1.10	1.04	8.33	7.35	5.60	
	CFHA	CFHC									2.40		1.91					1.80
M5x0.8	CHA	CHC	M5	-	-	10	12	16	20	25	1.60	7.93	1.10	1.04	8.89	7.90	6.40	
	CFHA	CFHC									2.40		1.91					1.80

所有尺寸：英寸

英制螺纹	螺纹尺寸 x 螺距	规格型号		螺纹 代码	长度“L” ± .015 (长度=长度编码/16英寸)						最小 板厚	沉孔 直径 +.003/ -.000	沉孔的 最小深度 Min.	A Max.	E ± .010	C Max.	孔中心 与安装 板边缘 最小距离	
		螺钉材料			.250	.375	.500	.625	.750	.875								1.00
		铝合金	不锈钢															
.112-40 (#4-40)	CHA	CHC	440	4	6	8	10	12	14	-	.062	.172	.043	.041	.205	.171	.156	
	CFHA	CFHC									.093		.075					.071
.138-32 (#6-32)	CHA	CHC	632	4	6	8	10	12	14	16	.062	.213	.043	.041	.250	.212	.188	
	CFHA	CFHC									.093		.075					.071
.164-32 (#8-32)	CHA	CHC	832	4	6	8	10	12	14	16	.062	.290	.043	.041	.328	.289	.219	
	CFHA	CFHC									.093		.075					.071
.190-32 (#10-32)	CHA	CHC	032	-	6	8	10	12	14	16	.062	.312	.043	.041	.350	.311	.250	
	CFHA	CFHC									.093		.075					.071